

Coated papers

Coated

Satinated

White Office Papers

Creative

Specials

MAC189 Top Coated Graphic⁺ Silk - FSC® 400 g/m²

Product Description

Top Coated Graphic⁺ Silk is a high quality vibrant coated paper suitable for graphic applications. The smooth surface provides sharp text and colour images. The consistent paper quality delivers excellent runnability.

Physical Properties

Weight (g/m ²)	400	ISO 536	Whiteness	127	CIE
Thickness (µm)	412	ISO 534	Opacity (%)	99,5	Elrepho
Brightness (%)	100	ISO 2470-2	Gloss Tappi 75° (%)	38	ISO 8254-1

Features

The smooth silk paper surface makes Top Coated Graphic⁺ Silk the ideal paper for applications such as high quality books, brochures, catalogues, direct mail, magazines and promotional communications.

Available Sizes

	SRA3
Grain direction	SG

LG = Long grain, SG = Short grain

Storage Conditions

Temperature 10 - 30 °C, Relative Humidity 20 - 70%
Repack opened reams or boxes when not in use.

Print Conditions

Acclimatize paper 24 hours before printing in print room conditions (preferably next to printer)
Best results are obtained between 15-25 °C and 30-65% RH (relative humidity)

Environment, Health & Safety

No Material Safety Data Sheet required.
ISO 9001 and 14001 certified production site.
ECF (Elemental Chlorine Free) bleaching technique for wood pulp.
Paper waste is suitable for recycling in most countries. Please refer to local paper recycle station.

Processing Guidelines, Tips & Tricks

Testing of customer application is always advised to secure proper print quality and perfect runnability.

Environmental Certification



Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2020

The Canon logo, consisting of the word "Canon" in a bold, red, sans-serif typeface.