

Films

Toner
<b>Water</b>
(eco) Solvent
UV Curable
Latex

# IJM366 PVC Display Film, Matt

## 220 µm

**Product Description** White, high-opacity, rigid PVC film with a matt, microporous coating for indoor roll-up displays and display stands.

<b>Physical Properties</b>	Thickness	220 µm	ISO 534
	Weight	295 g/m <sup>2</sup>	ISO 536

<b>Applications/features</b>	Roll-up displays	Roll-up displays
	Display stands	Display stands
	Exhibition panels	Exhibition panels
	Indoor signage	Indoor signage
	Posters	Posters
	Instant-dry, microporous coating	Instant-dry, microporous coating
	Brilliant colour reproduction	Brilliant colour reproduction
	Non-reflective matt surface	Non-reflective matt surface
	Suitable for dye and pigment inks	Suitable for dye and pigment inks
	Highly opaque, scratch resistant	Highly opaque, scratch resistant

<b>Available Widths (mm)</b>	2"core	594	841	914	1067						
	Refer for our current offering to <a href="http://www.canon-europe/mediaguide">www.canon-europe/mediaguide</a>										

**Storage Conditions** Shelf life: 1 year, Temperature 15-30°C, Relative Humidity 30-70%  
 Repack opened rolls when not in use.

**Print Conditions** Best results are obtained at 20°C and 65% RH.

**Environment, Health & Safety** No Material Safety Data Sheet required. No special hazards anticipated under normal conditions encountered in storage, processing and disposal. Waste disposal methods: incineration or landfill.

<b>Lamination Compatibility</b>	Cold	Warm	Hot	Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C -130°C
	yes	no	no	

**Outdoor Use** This film is not suitable for outdoor use.

**Colour Profiles** Canon develops high-quality colour profiles for media / ink / printer / RIP combinations. Check availability of profiles for your printer on [www.canon-europe/mediaguide](http://www.canon-europe/mediaguide)



---

**Processing  
Guidelines****Printing guidelines**

Side to be printed is the outer side of the roll. By nature the film induces a static charge when (un)winding, therefore precautions should be made to prevent this from influencing the print. Use of gloves is recommended. Make sure that the media does not come into contact with grease, oil, silicon, and dirt to avoid printing defects. Print results will vary for different printer/ink combinations. Canon media profiles include recommended ink/toner restrictions and printer parameters. Depending on environment and application, printer parameters may have to be adjusted slightly in order to obtain the best results.

**Application guidelines**

It is necessary to protect the surface if it is subject over a long time to abrasion or any other mechanical influences, to dirt or humidity. The lamination can be done right to the edges or over the edges. The user should check before using what is more appropriate.

We recommend to use self-adhesive laminating foils for cold lamination.

---

**Standard disclaimer:**

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.